



**Aputure
LS 600d Pro**



**Aputure
LS 600d**

Max Power Output	600W	
Max Power Draw	720W	
CCT	5600K	
CRI/TLCI	96+	
SSI (D56)	72+	
LUX @ 3m (5600k)	8,500	
Control Methods	On-board, 2.4G Remote, Sidus Link App, DMX512, Art-net via Ethernet, LumenRadio CRMX	On-board, 2.4G Remote ¹ , Sidus Link App, DMX512
0-100% Dimming	0.1% Increments	1% Increments
Weather Resistant	✓	—
LumenRadio CRMX	✓	—
Art-net (Ethernet)	✓	—
Multi-Voltage Battery Plates	Half Output with 2x V-Mount / Gold Mount Batteries (14.4V/15A, 26V/8.5A, 28.8V/7.5A)	
DC Input	48V/15A 3-Pin XLR DC Input	
Battery Charging	✓	—
Display Type	LCD Advanced UI	OLED Standard UI
Head Cable	LS 600 Series 5-Pin Weatherproof Head Cable (3m) Max Length 7.5m ²	
Built-in Lighting FX	8	
Bowens Mount	✓	
Curved Yoke	✓	
Carrying Case Included	✓	
Included Modifiers	LS 600 Series Hyper Reflector	
Mounting Pin	Junior/Baby (28mm/16mm)	
Weight (Lamp Head)	4.64kg / 10.23lbs	
Weight (Control Box)	5.8kg / 12.79lbs	3.24kg / 7.14lbs
Dimensions (Lamp Head)	30.8 x 25.03 x 45.6cm / 12.13 x 9.85 x 17.95in	
Dimensions (Control Box)	32.41 x 17.9 x 14.28cm / 12.76 x 7.05 x 5.62in	28.2 x 15.4 x 9cm / 11.1 x 6.1 x 3.54in

Photometrics LS 600d Pro / LS 600d

CCT	Distance	No Accessories	LS 600 Series Hyper Reflector	F10 Fresnel (Flood)	F10 Fresnel (Spot)
5600K	1M	22,150 lux / 2,057 fc	98,500 lux / 9,150 fc	89,200 lux / 8,286 fc	224,200 lux / 20,928 fc
	3M	2,600 lux / 241 fc	8,500 lux / 789 fc	11,440 lux / 1,062 fc	29,300 lux / 2,722 fc
	5M	1,020 lux / 94 fc	3,000 lux / 278 fc	4,260 lux / 395 fc	10,580 lux / 982 fc

¹VA-Remote RC1+ Not Included with LS 600d; ²LS 600 Series 5-Pin Weatherproof Head Cable (7.5m) Sold Separately